

ArchPro

The ArchPro is a mini-LED downlight featuring a discreet, low profile bezel with a deep matt black baffle as standard to minimise glare.

The ArchPro is also available with a soft light white baffle version for when a softer light is required, and the trim can be replaced with a trim-less version for a seamless integration of the luminaire with the surrounding architecture.

Colour:
Light Source:
Output:
Wattage:

White Trim.
LED.
See overleaf.
See overleaf.

Driver:
IP Rating:

HF, DALI.
IP44 Front, IP20 Rear.



Black Baffle



White Baffle



Trim-less



ArchPro

Black Baffle

Light Engine 1						
	Standard Beam Angle			Narrow Beam		
	2700K	3000K	4000K	2700K	3000K	4000K
Wattage (W)	8.2	6.2	6.2	8.2	6.2	6.2
Lumens* (lm)	542	593	627	565	618	653

Light Engine 2						
	Standard Beam Angle			Narrow Beam		
	2700K	3000K	4000K	2700K	3000K	4000K
Wattage (W)	10.2	8.2	8.2	10.2	8.2	8.2
Lumens* (lm)	753	767	811	785	800	845

Soft Light White Baffle

Light Engine 1						
	Standard Beam Angle			Narrow Beam		
	2700K	3000K	4000K	2700K	3000K	4000K
Wattage (W)	8.2	6.2	6.2	8.2	6.2	6.2
Lumens* (lm)	595	651	688	595	651	681

Light Engine 2						
	Standard Beam Angle			Narrow Beam		
	2700K	3000K	4000K	2700K	3000K	4000K
Wattage (W)	10.2	8.2	8.2	10.2	8.2	8.2
Lumens* (lm)	827	843	891	827	843	891

*Delivered Lumens

To specify choose one entry from each column, e.g., "ARP BB DD E3 LE1 SB 2700 WH" (option columns may be omitted if not required)

*Colour temperature tied to output (see above)

Name	Baffle	Control Gear	Emergency	Light Engine	Beam Angle	Colour Temp	Trim
ARP	BB (Black Baffle)	HF	E3 (3Hr)	LE1	SB (Standard)	2700	WH (White Bezel)
	WB (White Baffle)	DD (DALI)	ST3 (Self-Test)	LE2	NB (Narrow)	3000	TL (Trim-less)
			ED3 (DALI)			4000	



ArchPro

