



Eranu

Luminaires from the Eranu family can be surface mounted, suspended or wall mounted with direct or direct/indirect variation. Constructed from aluminium profile with opal diffuser.

Surface or suspended installation with direct light. With a choice of either an opal polycarbonate or micro-prismatic diffuser, they are available in five sizes:

Dimensions: 350 Sq., 600 Sq., 900 Sq., 1200x350 or 1500x350. x 70mm.
 Trim Options: White, Black, Brushed Aluminium or Anodised.
 Circuit Wattage: 350: 9w, 600/1200: 33w, 900: 73w or 1500: 41w.
 Output 3000K: 300: 1050lm, 600/1200: 4200lm, 900: 9460lm or 1500: 4270lm.
 Output 4000K: 300: 1080lm, 600/1200: 4340lm, 900: 9770lm or 1500: 4400lm.
 Efficacy 3000K: 300: 116.7, 600/1200: 127.3, 900: 129.6 or 1500: 104 LL/CW.
 Efficacy 4000K: 300: 120, 600/1200: 131.5, 900: 133.8 or 1500: 107.3 LL/CW.
 Construction: Aluminium/Polycarbonate.
 IP Rating: IP40.
 Driver: Electronic/DALI.



To specify choose one entry from each column below, e.g. "ER 606 D 840 WH" (option columns may be omitted if not required)

Name	Feature	Option	Emergency Option	Output (lm)	Colour Temp	Trim
ER (Eranu)	303 (300mm Sq.) 606 (600mm Sq.) 909 (900mm Sq.) 123 (1200mmx350mm) 153 (1500mmx350mm)	D (Dimmable)	EM EMS (Self Test) EMD (DALI)		830 840	WH (White) BK (Black) AL (Aluminium) AN (Anodised)