



Nautilus Extreme LED

The Nautilus is an IP66 rated, surface mounted, LED non-corrosive luminaire.

Suitable for areas such as warehouses, plantrooms & car parks.

*Please note the Nautilus Extreme LED must be mounted on a solid ceiling or wall which is covered over and protected from the elements. They should also not be installed in any rooms where oil is manipulated or where there is mineral and/ or vegetable oil vapour.

Colour:	Grey.
Length:	664mm, 1274mm, 1574mm.
Wattage:	12W, 24W, 30W, 47W, 59W.
Output:	L1 – 664mm 12W 1550lm, L2 – 664mm 24W 3136lm. L3 – 1274mm 24W 3136lm, L4 – 1274mm 47W 6095lm. L5 – 1574mm 30W 3900lm, L6 – 1574mm 59W 7602lm.
Light Source:	LED.
Construction:	Polycarbonate.
Mounting:	Surface*.
IP Rating:	IP66.
Driver:	Electronic/DALI.



	L	W
L1	664mm	90mm
L2	664mm	140mm
L3	1274mm	90mm
L4	1274mm	140mm
L5	1574mm	90mm
L6	1574mm	140mm

To specify choose one entry from each column below, e.g. "NAUX HF E3D L1 840 GR"

Name	Feature	Option	Emergency Option	Output (lm)	Colour Temp	Finish
NAUX(Nautilus Extreme)	HF DD (DALI)	-	E3 E3D (DALI)	L1	840	GR (Grey)
				L2	830	
				L3		
				L4		
				L5		
				L6		