

Nautilus LED

The Nautilus is a surface mounted LED non-corrosive luminaire, IP66 rated dust and moisture proof.

The Nautilus features a polycarbonate housing and opal polycarbonate diffuser.

IP66 & IK10 rated.

Please note the Nautilus LED must be mounted on a solid ceiling or wall which is covered over and protected from the elements. They should also not be installed in any rooms where oil is manipulated or where there is mineral and/ or vegetable oil vapour.

Light source:
Delivered Lumens:

Emergency lumens:
Circuit Wattage:

Efficacy: (lm/cW)

Colour Temp:

CRI:

Driver:

Dims:

IP Rating:

LED.

L1 2268lm,
L2 2674lm,
L3 3742lm,
L4 5348lm,
L5 4678lm,
L6 6685lm,
L7 8666lm.

500lm.

L1 15.3W, L2 18.6W, L3 26.1W, L4 36.7W,
L5 31.8W, L6 45.4W, L7 59W.

L1 148, L2 144, L3 143, L4 146,
L5 147, L6 147, L7 147.

4000K.

>80.

HF, DALI.

L1/ L2 662x96x111 (mm),
L3/ L4 1272x96x111 (mm),
L5/ L6/ L7 1572x96x111 (mm).
IP66.



To specify choose one entry from each column, e.g. "NAU DD E3 L1 840" (option columns may be omitted if not required)
Recessed as standard.

Name	Feature	Optional Mounting	Emergency Option	Output (lm)	Colour Temp
NAU	HF DD (DALI)	-	E3 ED3 (DALI EM)	L1 L2 L3 L4 L5 L6 L7	840