




# Sant

The Sant is an aluminium linear LED luminaire with an opal diffuser featuring a unique design. The luminaire can be dimmable with direct-indirect lighting and with the option of adjustable colour temperature, ranging between 2700K – 6500K.

Sant is an ideal solution when low power consumption, high efficiency and attractive design are required and may be used as a stand-alone or as a continuous lighting system. Measuring 66mm wide by 92mm high, the Sant is available in various lengths.

Length:	562mm, 842mm, 1122mm, 1402mm, 1682mm, 1962mm, 2242mm and 603mm x 603mm corner section.
Circuit Wattage: (Standard/Tuneable)	562: 10w, 842: 14w/20w, 1122: 19w/27w, 1402: 24w/34w, 1682: 28w/40w, 1962: 33w/47w, 2242: 38w/54w or 603: 19w/27w.
Output 3000K:	562: 970lm, 842: 1470lm, 1122: 1950lm, 1402: 2440lm, 1682: 2940lm, 1962: 3430lm, 2242: 3910lm or 603: 1950lm.
Output 4000K:	562: 1010lm, 842: 1520lm, 1122: 2020lm, 1402: 2530lm, 1682: 3040lm, 1962: 3550lm, 2242: 4050lm or 603: 2020lm.
Output Tuneable:	842: 1980lm, 1122: 2640lm, 1402: 3300lm, 1682: 3960lm, 1962: 4620lm, 2242: 5280lm or 603: 2640lm.
Efficacy 3000K:	562: 97, 842: 105, 1122: 102.6, 1402: 101.7, 1682: 105, 1962: 103.9, 2242: 102.9 or 603: 102.6 LL/CW.
Efficacy 4000K:	562: 101, 842: 108.6, 1122: 106.3, 1402: 105.4, 1682: 108, 1962: 107.6, 2242: 106.5 or 603: 106.3 LL/CW.
Efficacy Tuneable:	842: 99, 1122: 97.8, 1402: 97, 1682: 99, 1962: 98.3, 2242: 97.8 or 603: 97.8 LL/CW.
Construction:	Aluminium.
Trim Options:	White, Black, Anodised or Aluminium.
IP Rating:	IP20.
Driver:	Electronic/DALI.



To specify choose one entry from each column below, e.g. "SNT 1402 T BK"

Name	Length (mm)	Option	Emergency Option	Output (lm)	Colour Temp	Trim
SNT (Sant)	562	D (Dimmable)	EM		830	WH (White)
SNTC (Comer)	842		EMS (Self Test)		840	BK (Black)
	1122		EMD (DALI)		T (Tuneable)	AN (Anodised)
	1402					
	1682					
	1962					
	2242					
	603					

